

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
Revision Date 07/06/2026

Page 1 of 21
Print Date 07/07/2026

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Section 1. Identification

GHS product identifier : FP73820364-HIFORMER CART 140 COOL GRAY -
Chemical name : Mixture
CAS number : Mixture
Other means of identification : CC01104333
Product type : liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : **AVIENT CORPORATION**
 ColorMatrix Group Inc.
 680 North Rocky River Drive, Berea, Ohio, 44017-1628, USA
 +1 216 622 0100

Emergency telephone number (with hours of operation) : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SKIN SENSITIZATION - Category 1

GHS label elements

Hazard pictograms :



Signal word :

Warning

Hazard statements :

May cause an allergic skin reaction.

Precautionary statements

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
Revision Date 07/06/2026

Page 2 of 21
Print Date 07/07/2026

- Prevention** : Wear protective gloves. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.
- Response** : IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.
- Storage** : Not applicable.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazards not otherwise classified** : None known.
- Hazards identified when used** : No known significant effects or critical hazards.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Chemical name** : FP73820364-HIFORMER CART 140 COOL GRAY -
- Other means of identification** : FP73820364-HIFORMER CART 140 COOL GRAY -

Ingredient name	Synonyms	%	Identifiers
Titanium oxide	Titanium dioxide	>= 15 - <= 40	CAS: 13463-67-7
Limestone	Limestone	>= 10 - <= 30	CAS: 1317-65-3
White mineral oil (petroleum)	White mineral oil (petroleum)	>= 7 - <= 13	CAS: 8042-47-5
Decanedioic acid, 1,10-bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	>= 1 - <= 5	CAS: 41556-26-7
Carbon black	carbon black non-respirable	>= 1 - <= 5	CAS: 1333-86-4
Silica	silicon dioxide	>= 1 - <= 5	CAS: 7631-86-9
Aluminum oxide	aluminium oxide	>= 0.5 - <= 1.5	CAS: 1344-28-1
Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidinyl) ester	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	>= 0.5 - <= 1.5	CAS: 82919-37-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 3 of 21
 Print Date 07/07/2026

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 4 of 21
 Print Date 07/07/2026

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following: irritation, redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical or CO₂.
- Unsuitable extinguishing media** : None known.
- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon dioxide, carbon monoxide, nitrogen oxides, metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0

Page 5 of 21

Revision Date 07/06/2026

Print Date 07/07/2026

- suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 6 of 21
 Print Date 07/07/2026

also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

- : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Titanium oxide	<p>CAL OSHA PEL (2018-05-16). [titanium dioxide as Ti] TWA 8 hours: 10 mg/m3 (as Ti) Form: Total dust TWA 8 hours: 5 mg/m3 (as Ti) Form: Respirable fraction ACGIH TLV (2022-01-06). [titanium dioxide finescale particles] A3. TWA 8 hours: 2.5 mg/m3 Form: respirable fraction, finescale particles ACGIH TLV (2022-01-06). [titanium dioxide nanoscale particles] A3. TWA 8 hours: 0.2 mg/m3 Form: respirable fraction, nanoscale particles OSHA PEL 1989 (1989-03-01). [Titanium dioxide] TWA 8 hours: 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30). [Titanium dioxide] TWA 8 hours: 15 mg/m3 Form: Total dust</p>
Limestone	<p>CAL OSHA PEL (2018-05-16). [limestone] TWA 8 hours: 10 mg/m3 Form: Total dust TWA 8 hours: 5 mg/m3 Form: Respirable fraction OSHA PEL 1989 (1989-03-01). [Calcium carbonate] TWA 8 hours: 5 mg/m3 Form: Respirable fraction TWA 8 hours: 15 mg/m3 Form: Total dust OSHA PEL 1989 (1989-03-01). [Limestone] TWA 8 hours: 5 mg/m3 Form: Respirable fraction TWA 8 hours: 15 mg/m3 Form: Total dust OSHA PEL 1989 (1989-03-01). [Marble] TWA 8 hours: 5 mg/m3 Form: Respirable fraction</p>

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 7 of 21
 Print Date 07/07/2026

	<p>TWA 8 hours: 15 mg/m³ Form: Total dust OSHA PEL (1993-06-30). [Calcium Carbonate] TWA 8 hours: 5 mg/m³ Form: Respirable fraction TWA 8 hours: 15 mg/m³ Form: Total dust NIOSH REL (2015-02-13). [calcium carbonate] TWA 10 hours: 10 mg/m³ Form: Total TWA 10 hours: 5 mg/m³ Form: Respirable fraction</p>
White mineral oil (petroleum)	<p>OSHA PEL (1993-06-30). [Oil mist, mineral] TWA 8 hours: 5 mg/m³ NIOSH REL (2010-09-01). [OIL MIST MINERAL] TWA 10 hours: 5 mg/m³ Form: Mist STEL 15 minutes: 10 mg/m³ Form: Mist ACGIH TLV (2009-11-30). [Mineral Oil, pure, highly and severely refined] A4. TWA 8 hours: 5 mg/m³ Form: Inhalable fraction</p>
Decanedioic acid, 1,10-bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester	None.
Carbon black	<p>CAL OSHA PEL (2018-05-16). [carbon black] TWA 8 hours: 3.5 mg/m³ ACGIH TLV (2010-12-06). [Carbon black] A3. TWA 8 hours: 3 mg/m³ Form: Inhalable fraction NIOSH REL (2010-09-01). [carbon black] See Appendix A - NIOSH Potential Occupational Carcinogen. TWA 10 hours: 0.1 mg/m³ (as cyclohexane-extractable fraction) TWA 10 hours: 3.5 mg/m³ OSHA PEL 1989 (1989-03-01). [Carbon black] TWA 8 hours: 3.5 mg/m³ OSHA PEL (1993-06-30). [Carbon black] TWA 8 hours: 3.5 mg/m³</p>
Silica	<p>NIOSH REL (2010-09-01). [SILICA, AMORPHOUS] See Appendix A - NIOSH Potential Occupational Carcinogen. TWA 10 hours: 6 mg/m³</p>
Aluminum oxide	<p>CAL OSHA PEL (2018-05-16). [alumina] TWA 8 hours: 10 mg/m³ Form: Total dust TWA 8 hours: 5 mg/m³ Form: Respirable fraction OSHA PEL 1989 (1989-03-01). [.alpha.-Alumina] TWA 8 hours: 5 mg/m³ Form: Respirable fraction TWA 8 hours: 10 mg/m³ Form: Dust OSHA PEL (1993-06-30). [alpha-Alumina]</p>

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 8 of 21
 Print Date 07/07/2026

	<p>TWA 8 hours: 5 mg/m³ Form: Respirable fraction TWA 8 hours: 15 mg/m³ Form: Total dust NIOSH REL (2010-09-01). [aluminum pyro powders and welding fumes as Al] TWA 10 hours: 5 mg/m³ (Calculated as Al) Form: PYRO POWDERS AND WELDING FUMES CAL OSHA PEL (2018-05-16). [aluminum metal and oxide] TWA 8 hours: 10 mg/m³ Form: Total dust TWA 8 hours: 5 mg/m³ Form: Respirable fraction ACGIH TLV (2008-01-01). [Aluminum, metal and insoluble compounds] A4. TWA 8 hours: 1 mg/m³ Form: Respirable fraction</p>
<p>Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidinyl) ester</p>	<p>None.</p>

Biological exposure indices

No exposure indices known.

- Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 9 of 21
 Print Date 07/07/2026

parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : liquid [liquid]
- Color** : GREY
- Odor** : Faint odor.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Boiling point or initial boiling point and boiling range** : Not available.
- Flash point** : Not available.
- Evaporation rate** : Not available.
- Flammability** : Not available.
- Lower and upper explosion limit/flammability limit** : **Lower:** Not available.
Upper: Not available.
- Vapor pressure** : Not available.
- Relative vapor density** : Not available.
- Relative density** : Not available.

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 10 of 21
 Print Date 07/07/2026

- Solubility in water** : insoluble in water.
- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : **Dynamic** : Not available.
Kinematic : Not available.

Particle characteristics

- Median particle size** : Not applicable.

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Keep away from extreme heat and oxidizing agents.
- Incompatible materials** : Keep away from strong acids. Oxidizer.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result
Titanium oxide	Rabbit - Dermal - LD50 > 5,000 mg/kg

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 11 of 21
 Print Date 07/07/2026

	Rat - Male - Inhalation - LC50 Dusts and mists 6.82 Mg/l [4 h]
White mineral oil (petroleum)	Rat - Oral - LD50 5,000 mg/kg Rat - Dermal - LD50 2,000 mg/kg
Carbon black	Rat - Oral - LD50 15,400 mg/kg

Conclusion/Summary : Mixture.Not fully tested.

Skin corrosion/irritation

Conclusion/Summary : Mixture.Not fully tested.

Serious eye damage/eye irritation

Product/ingredient name	Result
Silica	Rabbit - Eyes - Mild irritant <u>Duration of treatment/exposure:</u> 24 hrs

Conclusion/Summary : Mixture.Not fully tested.

Respiratory corrosion/irritation

Conclusion/Summary : Mixture.Not fully tested.

Respiratory or skin sensitization

Skin

Conclusion/Summary : Mixture.Not fully tested.

Respiratory

Conclusion/Summary : Mixture.Not fully tested.

Germ cell mutagenicity

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 12 of 21
 Print Date 07/07/2026

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium oxide	-	2B	-
White mineral oil (petroleum)	-	-	-
Carbon black	-	2B	-
Silica	-	3	-
Aluminum oxide	-	-	-

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 13 of 21
 Print Date 07/07/2026

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following: irritation, redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Mixture. Not fully tested.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
FP73820364-HIFORMER CART 140 COOL GRAY -	107821.1 mg/kg	N/A	N/A	N/A	N/A
Titanium oxide	N/A	N/A	N/A	N/A	6.82 Mg/l
White mineral oil (petroleum)	5000 mg/kg	N/A	N/A	N/A	N/A
Carbon black	15400 mg/kg	N/A	N/A	N/A	N/A

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 14 of 21
 Print Date 07/07/2026

Section 12. Ecological information

Toxicity

Product/ingredient name	Result
Titanium oxide	Acute LC50 Marine water Fish - <i>Fundulus heteroclitus</i> > 1,000 Mg/l [96 h] Acute LC50 Fresh water Crustaceans - <i>Ceriodaphnia dubia</i> 3 Mg/l [48 h] Acute LC50 Fresh water Daphnia - <i>Daphnia pulex</i> 6.5 Mg/l [48 h]
Carbon black	Acute EC50 Fresh water Daphnia - <i>Daphnia magna</i> 37.563 Mg/l [48 h]
Aluminum oxide	Acute EC50 Fresh water Daphnia - <i>Daphnia magna</i> 114.357 Mg/l [48 h]

Conclusion/Summary : Not available.

Persistence and degradability

Not available.

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
White mineral oil (petroleum)	6	-	High

Mobility in soil

Soil/Water partition coefficient : Not available.

Other adverse effects

No known significant effects or critical hazards.

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 15 of 21
 Print Date 07/07/2026

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.
 IATA : Not classified as dangerous goods under transport regulations.
 IMDG : Not classified as dangerous goods under transport regulations.

Section 15. Regulatory information

U.S. Federal regulations

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

TSCA 12(b) - Chemical export notification

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Not listed
Clean Air Act Section 602 Class I Substances : Not listed
Clean Air Act Section 602 Class : Not listed

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 16 of 21
 Print Date 07/07/2026

II Substances

DEA List I Chemicals (Precursor Chemicals) : Not listed
DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : SKIN SENSITIZATION - Category 1

Composition/information on ingredients

Name	%	Classification
Decanedioic acid, 1,10-bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester	>= 1 - <= 5	SKIN SENSITIZATION - Category 1
Silica	>= 1 - <= 5	EYE IRRITATION - Category 2B
Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidinyl) ester	>= 0.5 - <= 1.5	SKIN SENSITIZATION - Category 1

SARA 313

Form R - Reporting requirements

Product name	CAS number	%
C.I. Pigment Yellow 119	68187-51-9	>= 1 - <= 5
Aluminum oxide	1344-28-1	>= 0.5 - <= 1.5

Supplier notification

Product name	CAS number	%
--------------	------------	---

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
Revision Date 07/06/2026

Page 17 of 21
Print Date 07/07/2026

C.I. Pigment Yellow 119	68187-51-9	>= 1 - <= 5
Aluminum oxide	1344-28-1	>= 0.5 - <= 1.5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed:
Titanium oxide
Limestone
White mineral oil (petroleum)
Carbon black
Silica
Aluminum oxide

New York : None of the components are listed.

New Jersey : The following components are listed:
TITANIUM DIOXIDE
CALCIUM CARBONATE
ZINC compounds
CARBON BLACK
ALUMINUM OXIDE

Pennsylvania : The following components are listed:
TITANIUM OXIDE
LIMESTONE
ZINC COMPOUNDS
CARBON BLACK
SILICA
ALUMINUM OXIDE

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Titanium dioxide, Carbon black, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-
Carbon black	-	-

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
Revision Date 07/06/2026

Page 18 of 21
Print Date 07/07/2026

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Chemical Weapons Convention List Schedule I Chemicals

None of the components are listed.

Chemical Weapons Convention List Schedule II Chemicals

None of the components are listed.

Chemical Weapons Convention List Schedule III Chemicals

None of the components are listed.

Montreal Protocol

None of the components are listed.

Stockholm Convention on Persistent Organic Pollutants

Annex A - Elimination - Production

None of the components are listed.

Annex A - Elimination - Use

None of the components are listed.

Annex B - Restriction - Production

None of the components are listed.

Annex B - Restriction - Use

None of the components are listed.

Annex C - Unintentional - Production

None of the components are listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Rotterdam Convention on Prior Informed Consent (PIC) - Industrial

None of the components are listed.

Rotterdam Convention on Prior Informed Consent (PIC) - Pesticide

None of the components are listed.

Rotterdam Convention on Prior Informed Consent (PIC) -Severely hazardous pesticide

None of the components are listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
 Revision Date 07/06/2026

Page 19 of 21
 Print Date 07/07/2026

Heavy metals - Annex 1

None of the components are listed.

POPs - Annex 1 - Production

None of the components are listed.

POPs - Annex 1 - Use

None of the components are listed.

POPs - Annex 2

None of the components are listed.

POPs - Annex 3

None of the components are listed.

Inventory list

- Australia** : All components are listed or exempted.
- Canada** : At least one component is not listed in DSL but all such components are listed in NDSL.
- China** : All components are listed or exempted.
- Eurasian Economic Union** : **Russian Federation inventory:** Not determined.
- Japan** : **Japan inventory (CSCL):** Not determined.
Japan inventory (ISHL): Not determined.
- New Zealand** : All components are listed or exempted.
- Philippines** : All components are listed or exempted.
- Republic of Korea** : Not determined.
- Taiwan** : All components are listed or exempted.
- Thailand** : Not determined.
- Turkey** : Not determined.
- United States** : All components are active or exempted.
- Viet Nam** : Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to

SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -


Version Number 1.0
 Revision Date 07/06/2026

Page 20 of 21
 Print Date 07/07/2026

provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Procedure used to derive the classification

Classification	Justification
SKIN SENSITIZATION - Category 1	Calculation method

History

- Date of printing : 07/07/2026
- Date of issue/Date of revision : 07/06/2026
- Date of previous issue : 00/00/0000
- Version : 1.0
- Prepared by : VISWANATHANL
- Key to abbreviations :
 - ATE = Acute Toxicity Estimate
 - BCF = Bioconcentration Factor
 - DOT = Department of Transportation
 - GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 - IATA = International Air Transport Association
 - IBC = Intermediate Bulk Container
 - IMDG = International Maritime Dangerous Goods
 - IMO = International Maritime Organization
 - LogPow = logarithm of the octanol/water partition coefficient
 - MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 - N/A = Not available
 - SGG = Segregation Group
 - TDG = Transportation of Dangerous Goods
 - UN = United Nations
- References : Not available.

Notice to reader



SAFETY DATA SHEET

FP73820364-HIFORMER CART 140 COOL GRAY -

Version Number 1.0
Revision Date 07/06/2026

Page 21 of 21
Print Date 07/07/2026

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.